



Automatic Cabinet Doors™

| | |
|--|---|
| Models | Single Panel, Dual Panel , Dual Guillotine Panel, Three Panel. All systems are custom designed. |
| Price | Quoted prices available upon request |
| Types | Flush Mount – Moving door is in same plane as fixed panels surrounding it. The door must tilt back then go up behind the fixed panel that is above the opening (Closed Flush) |
| | Non Flush – Doors go straight up and down. No tilting |
| System Description | Vertical lifting only / strap(belt) driven with motor tube |
| Sizes | From 20 inches wide to 96 inches wide. Special sizes available |
| Lift Capacity | Most systems are for 10 pounds to 200 pounds |
| Controls | 120 Volt Wall Switch, Remote Control , Low voltage wall switch, Dry contacts for Home Automation Integration |
| Cabinet Requirements (Depth needed behind the door if closed flush) | Single Panel Flush mount doors need depth of approx. 3 inches when tilting back and moving up if 30 inch high opening. (Depth needed in front of TV) |
| | Dual Panel Flush Mount doors need depth of approx. 5.5 inches when tilting back and moving up if 30 inch high opening. (Depth needed in front of TV) |
| | Three Panel Flush Mount doors need depth of approx. 7 inches when tilting back and moving up if 40 inch high opening. (Depth needed in front of TV) |
| Cabinet Requirements (Total Depth, Width and Height) | Height required is 3 to 4 inches greater than the height of the panels. The more panels used in the design the less height required. |
| | Depth needed is approx 7 inches for single doors and up to 14 inches for 3 panel doors. This is to ensure there is space for the motor tube and the doors. The motor tube with lifting straps is 3 inch diameter for single, 5 inch for dual doors and 7 inches for three panel doors |
| | Width required is the door width plus 1 1/2 inches on each side for the guides. Total width required is the door or panel width plus a Minimum of 3 inches. |
| Electrical: | 120 watts , usually about 2 amps but depends on door size/ 6 foot motor cord with plug |
| Warranty: | 3 years parts and labor |
| | |