



Automatic Cabinet Doors™ - Model Details

MODEL NAME	DETAILS
1 Panel Straight	Minimum depth required at motor tube – Approx. 4 inches
	Guides are 1 ½ wide and 2 ½ deep and are placed outside of door opening
	Door moves straight up and down and no space behind door is required.
1 Panel Closed Flush	Minimum depth required at motor tube – Approx. 8 inches
	Guides are 1 ½ wide and 4 1/2 to 5 1/2 deep and are placed outside of door opening
	Door tilts back as it raises. 2.5 for smaller doors (24 inch high) and 3.5 inches for taller doors (48 inches high)
	A 60 degree chamfer is required on the fixed panel above the opening
1 Panel Straight Open	Minimum depth required at motor tube – Approx. 4 inches
	Guides are 1 ½ wide and 2 ½ deep and are placed outside of door opening.
	Face frame on the sides of cabinet needs to be 3.5 (minimum) on the inside to hide lifting straps
	If door and face frame are to be in the same plane then roller assembly extensions are required. The lifting strap would attach to the extension.
2 Panel Straight	Minimum depth required at motor tube – Approx. 7 inches
	Guides are 1 ½ wide and 5 inches deep and are placed outside of door opening
	Door moves straight up and down and no space behind door is required.
2 Panel Closed Flush	Minimum depth required at motor tube – Approx. 10 inches
	Guides are 1 ½ wide and 5 1/2 deep and are placed outside of door opening
	Door panels tilt back 5 inches as they move up.
	A 60 degree chamfer is required on the fixed panel above the opening
2 Panel Straight Guillotine	Minimum depth required at motor tube – Approx. 4 inches
	Guides are 1 ½ wide and 2 ½ deep and are placed outside of door opening.
	Face frame on the sides of cabinet needs to be 3.5 (minimum) on the inside to hide lifting straps
2 Panel Closed Flush Guillotine	Minimum depth required at motor tube – Approx. 8 inches
	Guides are 1 ½ wide and 4 1/2 to 5 1/2 deep and are placed outside of door opening.
	Face frame on the sides of cabinet needs to be 4.5 (minimum) on the inside to hide lifting straps.
	Doors tilt back as they raise and lower 2.5 inches
	A 60 degree chamfer is required above and below the opening.
3 Panel Straight 3 Panel Closed Flush	Contact StorageMotion Inc. directly for details