

Automatic Cabinet DoorsTM

Styles Available	Single Panel, Dual Panel, Dual Guillotine Panel, Three Panel. All systems are custom designed.
Price	Quoted prices available upon request
Types	Closed Flush – Moving door is in same plane as fixed panels surrounding it. The door must tilt back then go up behind the fixed panel that is above the opening (Closed Flush) Straight – Doors go straight up and down. No tilting
	Straight Open – door have an open area above that is available for use when the door is closed.
System Description	Vertical lifting only / Lifting strap driven with motor tube. All models have doors stored above but some models allow for doors to move down and be stored below.
Sizes	From 20 inches wide to 96 inches wide. Special sizes available
Lift Capacity	Most systems are for 10 pounds to 200 pounds
Lifting Position	The door/panel starting and stopping positions are set through the motor limits which are set with pushbuttons on the motor.
Controls	120 Volt Wall Switch, RFQ and IR Remote Control , Low voltage wall switch, Dry contacts for Home Automation Integration
Electrical	120 volts, usually about 2 amps but depends on door size/ 6 foot motor cord with plug.
Safety	Photo eyes are available for most units but must be requested. There is an additional charge for photo eyes which will require a special controller
Motor Protection	The motor is rated as intermittent use only and will shut off temporarily if it gets too hot. The motor also has jam protection where it will also shut off temporarily if it is starts to draw a spike in electrical current.
Warranty	3 years parts and labor

StorageMotion,Inc. <u>www.storagemotion.com</u> p.704-746 3700 f. effective 2-2018